

The 3M logo is displayed in its characteristic red, bold, sans-serif font.The VHB Tape logo features the letters 'VHB' in a large, bold, black font with a white outline, and the word 'Tape' in a smaller, black font below it. To the right of 'VHB' is a small 'TM' trademark symbol. Below the word 'Tape' is the text 'Since 1980' in an even smaller font.A person wearing a white protective suit and gloves is using a heat gun on a metal structure. The scene is set in a high-temperature environment, likely a furnace or industrial oven, with a strong orange and red glow. The person is holding the heat gun with their right hand, and the nozzle is directed towards a metal frame. The frame has several rectangular cutouts. The background shows the interior of the furnace with various metal components and a bright light source.

Take on the most demanding high temperature applications with the new 3M™ VHB™ Tape GPH series.

3M™ VHB™ Tape GPH Series

The new 3M™ VHB™ Tape GPH series is a permanent bonding solution that can replace traditional mechanical fasteners and liquid adhesives in challenging, high temperature applications. It uses a conformable, acrylic foam core to provide a good balance of strength and conformability. The 3M™ VHB™ Tape GPH series has excellent temperature resistance, making it ideal for permanent bonding where high temperature tolerance is needed, including applications that undergo a powder coat or liquid painting process.

Features

- Good adhesion to high and medium surface energy materials (metals, glass, plastics) as well as many coated or painted surfaces
- Excellent temperature resistance (short term 450°F and long term 300°F)
- Good solvent resistance
- High initial tack providing strong immediate handling strength
- Conformable foam offers good gap filling and stress relaxation

High Temperature Applications



3M™ VHB™ Tape GPH's high temperature resistance allows it to be bonded prior to powder coat or liquid painting processes. This reduces the number of "touches," leading to a more streamlined manufacturing process.



The new GPH series offers the speed and ease assembly found in 3M™ VHB™ Tape, even in applications that require long durations of high temperature exposure.

	Product	Thickness	Color	Dimensions	3M ID
	3M™ VHB™ GPH-060GF	0.6mm	Grey	12mm x 33m	70-0075-1772-8
				19mm x 33m	70-0075-1173-6
				25mm x 33m	70-0075-1774-4
				MISC Custom Sizes	70-0002-4211-8
	3M™ VHB™ GPH-110GF	1.1mm	Grey	12mm x 33m	70-0075-1779-3
				19mm x 33m	70-0075-1780-1
				25mm x 33m	70-0075-1781-9
				MISC Custom Sizes	70-0002-4209-2
	3M™ VHB™ GPH-160GF	1.6mm	Grey	12mm x 33m	70-0075-1785-0
				19mm x 33m	70-0075-1786-8
				25mm x 33m	70-0075-1788-4
				MISC Custom Sizes	70-0002-4210-0



Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144 USA

Phone 1-800-362-3550
Web 3M.com/VHB

For more information about 3M™ VHB™ Tape GPH, contact your local sales representative or visit 3M.com/VHB.

3M and VHB are trademarks of 3M Company.
Please recycle. Printed in USA.
© 3M 2018. All rights reserved.
78-9236-7288-1 Rev-0518

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.