

Product Line


AMAZING CONNECTIONS™






Usage Guide

Index







VELCRO® Brand Product Line

- Textile Hook & Loop Tapes
- Plastic Hook Tapes
- Self-engaging Hook & Loop Tapes
- Specialties
- Converted Products
- Concepts
- Complementary Information



Textile Hook & Loop Tapes

- 14	n	n	Ľ	
п	υ	U	n	

Woven Hooks Hook 88 Hook 65 Hook 84 Hook 89 Hook 66 HI-AIR® Hook 46 HI-GARDE®

Hook 81 Polyester Woven Mushrooms VEL-LOC[®] 085 SUPER VEL-LOC® 083 SUPER VEL-LOC[®] Quadrilobal 87S

LOOP

Woven Loops

Loop 1000 Loop 1100 Loop 2000 Loop 4000 Loop 3000 HI-AIR® Loop 8000 HI-GARDE® Loop 9000 Polyester VELSTRECH® Loop 151

Knitted Loops

Loop 3001 Loop 3003 Loop 3610 Loop 3607 Loop 3368 Loop 3905 Loop 3707 Loop 3900 Loop 3200 Elastic Loop 152

Nonwoven Loops FNL 264

FNL 403

Shape 15

Hook 704

Hook 705

Hook 706

Hook 711

Hook 719

Hook 745

Hook 748

Hook 805

Hook 742 Hook 810

Hook 811

Hook 845

Hook 848

Hook 886

Hook 887

Hook 733

Hook 752

Hook 757

Hook 822

Hook 830

Hook 833

Hook 511

Hook 819

Hook 744

Hook 841

Hook 732 Hook 788

Hook 798 Hook 847

Shape 108

Shape 24

Shape 29

Shape 66

Shape 97

Shape 99

Shape 22

Plastic Hook Tapes



Self-engaging Hook & Loop Tapes

HOOK & LOOP ON OPPOSITE SIDES

Full width Hook coverage Double Face 200 Back to back Hook & Loop ONE-WRAP® **ONE-WRAP®** Fire Retardant QWIK-TIE BUNDLE TIE

Single Hook lane FLEX-ZONE[™] 3610 FLEX-ZONE[™] 3905

HOOK & LOOP ON THE SAME SIDE Hook & Loop mixed OMNI-TAPE®



Specialties

φŸ MEDICAL Double Faced Loops DFL-S (Sewn) DFL-B (Bonded) DFL-E (Embossed) DFL-EC J-Wrap

17

PACKAGING Flexible Packaging PRESS-LOK® 775 PRESS-LOK® 776 PRESS-LOK® 779 PRESS-LOK® 731 (Adhesive 9932) Touch & Seal Closure (Weldable)

BERSONAL CARE

Diaper TABs Hook 701

i TRANSPORTATION

AUTOMOTIVE

Seating Hooks DCS 36 (Centre Slit) DCS 36 (End Tab) MIGG 15 MIGG 15-1 HF3 Flex-MIGG

Seating Loops Loop Auto Standard

Loop Auto MIGG

Interior Parts Burr Hook



Converted Products

SHAPES **VELCOIN®**

Easy Coin (PS-32, 1-3/8" x 1/2") PRESS-LOK[®] 731 (PS-32, 0.4 x 0.8")

STRAPS

VELSTRAP[®], Facestrap, Backstrap ONE-WRAP[®] Strap ONE-WRAP[®] Strap Fire Retardant QWIK-TIE Strap System Strap LogiStrap®

LAMINATES VELTEX®

Velcro[®]



Self-Engaging PRESS-LOK[®] Hook Fish Scale Hook SC2



Complementary Information

Hook & Loop Color Capabilities Plastic Hook Shapes Adhesives Converting & Packaging Laminates



Textile Hook & Loop Tapes





VELCR0® Brand		TYPES OF ENGAGEMENT
Hook 88		WOVEN HOOK
 Base material: Nylon Standard colors: Hook 88 & Loop 1000 color chart 		WOVEN MUSHROOM
 Standard widths (inches): 1/2, 5/8, 3/4, 1, 1-1/2, 2, 4, 6 Standard put-ups: 25 yd rolls, 50 yd rolls 		
 Suggested mating component: Loop 1000 Cycle life: High 		PLASTIC HOOK & LOOP/VELOUR MAGNETIC ATTRACTION
Main applications Apparel, cable management, panels, orthopedic braces, seat trim, aviation, furnishing, straps.		PLASTIC HOOK & NONWOVEN LOOP
Other applications requiring high cycle life closure.		PLASTIC HOOK SHAPES
â îi 💞 🛡 💼 🗧 😫 🗱		
		AVAILABLE WITH PRESSURE AVAILABLE WITH F.R.T. TREATMENT
VELCRO® Brand Hook 65		SENSITIVE ADHESIVE F.R.T. treatment (meets FAR 25.853, MVSS 302)
• Base material: Nylon		WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
 Standard colors: Black, white Standard widths (inches): 5/8, 3/4, 1, 1-1/2, 2, 4 Standard put-ups: 25 yd rolls, 50 yd rolls 		
Suggested mating component: Loop 2000 Cycle life: High		SPECIAL CHARACTERISTICS
Main applications		COLOR FASTNESS
Apparel, blood pressure cuffs, orthopedics, straps.		SHRINKAGE RESISTANCE WASHABLE AT HIGH
		PRINTING OPTIONS
		ABC CUSTOMIZED PRINTING
		COLORS
VELCRO® Brand Hook 84		HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS
Base material: Nylon Standard colors: Black, white		
 Standard widths (inches): 3/4, 1, 1-3/16, 2, scored pieces Standard put-ups: 50 yd rolls 		
 Suggested mating component: Loop 1000 Cycle life: Medium 		
Main applications		
Footwear, automotive interiors, heavy duty industrial uses. Other applications requiring high peel and shear performance.		APPLICATIONS
		APPAREL CONSTRUCTION MEDICAL MILITARY &
ÎR 🖑 🗘 🖆 🛨 🚘 米	B ABC	
		PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES



		CHARACTERISTICS
VELCRO [®] Brand		TYPES OF ENGAGEMENT
Hook 89		WOVEN HOOK
 Base material: Nylon Standard colors: Black, coyote, foliage green, tan Standard widths (inches): 5/8, 3/4, 1, 1-1/2, 2, 4 		& WOVEN LOOP WOVEN MUSHROOM & LOOP/VELOUR Self-ENGAGING HOOK & LOOP
 Standard put-ups: 50 yd rolls Suggested mating component: Loop 1100 		PLASTIC HOOK & LOOP/VELOUR MAGNETIC ATTRACTION
Cycle life: High Main applications		PLASTIC HOOK & NONWOVEN LOOP
Professional apparel (military, firefighters, etc.), reusable diapers, mop heads. Other applications requiring IR resistance.		
		PLASTIC HOOK SHAPES
â Tr 💞 💟 🖀 🚼 🕿 🗶	3 🔪 💷 🐹 🔀 🛃 日	
		ADHESIVES & FRT TREATMENTS
VELCRO® Brand Hook 66 HI-AIR®		AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE X F.R.T. treatment (meets FAR 25.863, MVSS 302)
• Base material: Nylon, NOMEX [®] fibers ¹		SSS WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
 Standard colors: Natural, camouflage Standard widths (inches): 1, 2 		
 Standard put-ups: 50 yd rolls Suggested mating component: Loop 3000 HI-AIR® 		SPECIAL CHARACTERISTICS
Cycle life: Medium Main applications		COLOR FASTNESS WEATHER RESISTANCE
Self-extinguishing garments, military apparel, transportation interiors. Other applications requiring to meet military and fire retardant		SHRINKAGE RESISTANCE WASHABLE AT HIGH
specifications.		
¹ NOMEX® is a Reg. TM of E.I. du Pont de Nemours and Company.		
	3	ABC CUSTOMIZED PRINTING
		COLORS
VELCRO® Brand Hook 46 HI-GARDE®	12222222222222222222222222222222222222	HALL HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS
Base material: Stainless Steel		
 Standard colors: Steel grey Standard widths (inches): 1 		
Standard put-ups: 25 yd rolls Suggested mating component: Loop 8000 HI-GARDE®		
Cycle life: Low Main applications		
Egress curtain, aircraft thermal blankets and pipe wraps. Other applications requiring extreme temperature and corrosion resistance.		APPLICATIONS
		APPAREL CONSTRUCTION MEDICAL MILITARY &
1 i i i i i i i i i i i i i i i i i i i	3	
		PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES
AMERICAS PRODUCT LINE	<code>VELCRO®</code> and other marks are owned by Velcro Industries B.V. © 2015	




CHARACTERISTICS

PACKAGING

PERSONAL CARE TRANSPORTATION

SPECIALTIES

VELCRO® Brand	TYPES OF ENGAGEMENT
VELCRO® Brand Hook 81 Polyester	WOVEN HOOK & WOVEN LOOP SELF-ENGAGING HOOK
 Base material: Polyester Standard colors: Black, white, camouflage Standard widths (inches): 3/4, 1, 1-1/2, 2 	WOVEN MUSHROOM & LOOP/VELOUR SELF-ENGAGING HOOK & LOOP
Standard put-ups: 25 yd rolls Suggested mating component: Loop 9000 Polyester	PLASTIC HOOK & LOOP/VELOUR NIS MAGNETIC ATTRACTION
• Cycle life: Medium	PLASTIC HOOK & NONWOVEN LOOP
Main applications Apparel, outdoor applications, transportation interiors.	
Other applications requiring weather (moist, UV) resistance.	PLASTIC HOOK SHAPES
	ADHESIVES & FRT TREATMENTS
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE F.R.T. treatment (meets FAR 25.853, MVSS 302)
	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
	SPECIAL CHARACTERISTICS
	COLOR FASTNESS
	SHRINKAGE RESISTANCE WASHABLE AT HIGH
Charling and and and a state of the second sec	PRINTING OPTIONS
	ABC CUSTOMIZED PRINTING
	COLORS
	HALE HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS
- Contraction	
	APPLICATIONS
	APPAREL CONSTRUCTION MEDICAL MILITARY &





VELCRO [®] Brand		TYPES OF ENGAGEMENT
Loop 1000		WOVEN HOOK & WOVEN LOOP
 Base material: Nylon Standard colors: Hook 88 & Loop 1000 color chart Standard widths (inches): 1/2, 5/8, 3/4, 1, 1-1/2, 2, 4, 6 		WOVEN MUSHROOM & LOOP/VELOUR SELF-ENGAGING HOOK & LOOP
 Standard widths (incres): 1/2, 5/8, 5/4, 1, 1-1/2, 2, 4, 6 Standard put-ups: 25 yd rolls, 50 yd rolls Suggested mating component: Hook 88 		
• Cycle life: High		
Main applications Apparel, cable management, panels, orthopedic braces, seat trim, aviation, furnishing, straps.		PLASTIC HOOK & NONWOVEN LOOP
Other applications requiring high cycle life closure.		PLASTIC HOOK SHAPES
	The second of the Contraction of the	
â îi 💞 文 💼 🗧 🗱		ADHESIVES & FRT TREATMENTS
VELCRO® Brand		AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE ADHESIVE ADHESIVE SENSITIVE ADHESIVE
Loop 1100		SSS WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
 Base material: Nylon Standard colors: Black, coyote, foliage green, tan Standard widths (inches): 5/8, 3/4, 1, 1-1/2, 2, 4 		OR REACTIVATION METHOD
 Standard put-ups: 50 yd rolls Suggested mating component: Hook 89 		SPECIAL CHARACTERISTICS
• Cycle life: High		COLOR FASTNESS WEATHER RESISTANCE
Main applications Professional apparel (military, firefighters, etc.), reusable diapers, mop heads. Other applications requiring IR resistance.		SHRINKAGE RESISTANCE WASHABLE AT HIGH TEMPERATURES
		PRINTING OPTIONS
		ABC CUSTOMIZED PRINTING
â 11 8 💟 î 🚼 🖻 🗶		
VELCRO [®] Brand		
Loop 2000		HELE HOOK 88 & LOOP 1000 COLOR CHART
 Base material: Nylon Standard colors: Black, white Standard widths (inches): 5/8, 1, 1-1/2, 2, 4 		
 Standard put-ups: 50 yd rolls Suggested mating component: Hook 65 Cycle life: High 		
Main applications		
Apparel, blood pressure cuffs, transportation interiors, mop heads. Other applications requiring low shrinkage.		APPLICATIONS
	加速使影響使研究等性存在	APPAREL CONSTRUCTION MEDICAL MILITARY &
â îi 💕 🗘 î 🗧 🕿 米		GOVERNMENT
		PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES



CHARACTERISTICS

VELCRO® Brand LOOP 40000 9 Base material: Nylon 9 Standard colors: Black 9 Standard widths (inches): 3/4, 1, 2 9 Standard put-ups: 50 yd rolls 9 Suggested mating component: Hook 841 9 Cycle life: High Main applications Sports gear, adventurer apparel, performance footwear, outwear. Other applications requiring a low profile clsoure.			TYPES OF ENGAGEMENT WOYEN HOOK & WOYEN LOOP WOYEN MUSHROOM & LOOPVELOUR WOYEN MUSHROOM & LOOPVELOUR PLASTIC HOOK & LOOPVELOUR PLASTIC HOOK & NONWOVEN LOOP PLASTIC HOOK & NONWOVEN LOOP
			00 00 <td< td=""></td<>
VELCRO® Brand LOOP 3000 HI-AIR® • Base material: Nylon / NOMEX® fibers ¹ • Standard colors: Natural, camouflage • Standard widths (inches): 1, 2 • Standard put-ups: 50 yd rolls • Suggested mating component: Hook 66 HI-AIR® • Cycle life: Medium Main applications Self-extinguishing garments, military apparel, transportation interiors. Other applications requiring to meet military and fire retardant specifications.			Image: Angle with pressure subscription of the state
			COLORS
VELCRO® Brand LOOP 8000 HI-GARDE® • Base material: Stainless steel • Standard colors: Steel grey • Standard widths (inches): 1 • Standard put-ups: 25 yd rolls • Suggested mating component: Hook 46 HI-GARDE® • Cycle life: Low			HELE HOOK 88 & LOOP 1000 COLOR CHART
Main applications Egress curtain, aircraft thermal blankets and pipe wraps. Other applications requiring extreme temperature and corrosion resistance.		-	APPLICATIONS
🚺 🗳 🖆 🕇 🚘 米	3	П	Image: ApparelImage: ConstructionImage: ConstructionImage: ConstructionImage: ConstructionImage: Apparel

AMERICAS PRODUCT LINE



VELCRO® Brand			TYPES OF ENGAGEMENT	
Loop 9000 Polyester			WOVEN HOOK & WOVEN LOOP	SELF-ENGAGING HOOK
 Base material: Polyester Standard colors: Black, white, camouflage Standard widths (inches): 3/4, 1, 1-1/2, 2 			WOVEN MUSHROOM & LOOP/VELOUR	SELF-ENGAGING HOOK & LOOP
 Standard put-ups: 25 yd rolls Suggested mating component: Hook 81 Polyester 			PLASTIC HOOK & LOOP/VELOUR	MAGNETIC ATTRACTION
Cycle life: Medium Main applications			PLASTIC HOOK & NONWOVEN LOOP	
Apparel, outdoor applications, transportation interiors. Other applications requiring weather (moist, UV) resistance.				
			PLASTIC HOOK SHAPES	
Certified to AA55126B				
航 👔 💞 🐨 📅 🗟 🔭 米	<u>بې</u> کې درو	ABC		
			ADHESIVES & FRT TREATMENTS	
VELCRO® Brand		85.12	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE	AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
VELSTRETCH [®] Loop 151			WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	
 Base material: Nylon, elastomer Standard colors: Black, white, beige, ink blue, royal blue Standard widths (inches): 5/8, 3/4, 1, 1-1/2, 2 				
 Standard widths (miches): 3/8, 3/4, 1, 1-1/2, 2 Standard put-ups: 40 yd rolls Suggested mating component: Hook 65, Hook 845 			SPECIAL CHARACTERISTICS	
• Cycle life: Medium			COLOR FASTNESS	weather resistance
Main applications Elastic straps, fetal monitoring belts, headgears, soccer shin			SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
guards, scuba diving equipment straps. Other applications requiring an elastic loop providing comfort				
as well as a secure fit.			PRINTING OPTIONS	
			ABC CUSTOMIZED PRINTING	
â î <mark>8</mark> 🗘 12 🗧 🛪 米	3			
			COLORS	
			HOOK 88 & LOOP 1000 COLOR CHART	AVAILABLE COLORS
	T			
	4			
		10 0 00 00 00	APPLICATIONS	
			APPAREL CONSTRUCTION	DN MEDICAL MILITARY & GOVERNMENT
	and and a		1	
		and a second	PACKAGING PERSONAL CA	RE TRANSPORTATION SPECIALTIES
		alana la duatrias R.V. @ 2015		



CHARACTERISTICS

5

0

NS

00 BURR

8

َشْ

SELF-ENGAGING HOOK

MAGNETIC ATTRACTION

SELF-ENGAGING HOOK & LOOP

AVAILABLE WITH F.R.T. TREATMENT

WEATHER RESISTANCE

WASHABLE AT HIGH TEMPERATURES

AVAILABLE COLORS

٥Ÿ

MEDICAL

TRANSPORTATION

 \bigcirc MILITARY & GOVERNMENT

*

SPECIALTIES

UNIDIRECTIONAL

VELCRO [®] Brand		TYPES OF ENGAGEMENT
Loop 3001		WOVEN HOOK
Base material: Nylon Standard colors: Black, white		WOVEN MUSHROOM
 Standard widths (inches): Up to 54 Standard put-ups: 25 yd rolls, 50 yd rolls 		
 Suggested mating component: Hook 88 Cycle life: High / Medium 		PLASTIC HOOK & LOOP/VELOUR
Main applications		PLASTIC HOOK & NONWOVEN LOOP
Technical apparel, solar panels, back belt support, orthopedic braces, respiratory headgear, fabricated items.		
Other applications requiring high cycle life.		PLASTIC HOOK SHAPES
	ABC	
		ADHESIVES & FRT TREATMENTS
		 AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE
VELCRO® Brand		
• Base material: Nylon		SSS WELDABLE BY HEAI, SOLVENT OR REACTIVATION METHOD
 Standard colors: Black, white Standard widths (inches): Up to 57 		
 Standard put-ups: 40 yd rolls, 60 yd rolls Suggested mating component: Hook 88 		
• Cycle life: High / Medium		COLOR FASTNESS
Main applications Technical apparel, solar panels, back belt support, orthopedic braces,		SHRINKAGE RESISTANCE
respiratory headgear, fabricated items. Other applications requiring high cycle life.		
		PRINTING OPTIONS
		ABC CUSTOMIZED PRINTING
		 COLORS
VELCRO [®] Brand		H&L HOOK 88 & LOOP 1000
Loop 3610 • Base material: Nylon		COLOR CHART
Standard colors: Black, white, beige		
 Standard widths (inches): Up to 50 Standard put-ups: 50 yd rolls, 100 yd rolls Suggested mating component: Hook 845 		
• Cycle life: Medium		
Main applications Apparel, orthopedic braces, respiratory headgear, materials handling,		
transportation interiors, moulding, cleaning products.		APPLICATIONS
		APPAREL CONSTRUCTION
â î 💞 💙 🛅 🚼 🚘 米	ABC	
		PACKAGING PERSONAL CARE



5

0

NS

X

Č,

SELF-ENGAGING HOOK

MAGNETIC ATTRACTION

SELF-ENGAGING HOOK & LOOP

UNIDIRECTIONAL

AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)

WEATHER RESISTANCE

AVAILABLE COLORS

Ý

MEDICAL

TRANSPORTATION

 \bigcirc

MILITARY & GOVERNMENT

*

SPECIALTIES

WASHABLE AT HIGH TEMPERATURES

VELCRO® Brand Loop 3607			PES OF ENGAGEMENT
 Base material: Nylon / Backing PVC film Standard colors: Black, white 			WOVEN HOOK & WOVEN LOOP
 Standard widths (inches): Up to 6 Standard put-ups: 50 yd rolls Suggested mating component: Hook 848 			L LOOP/VELOUR
Cycle life: Medium Main applications			PLASTIC HOOK & NONWOVEN LOOP
Blood pressure cuffs, vinyl pouches. Other weldable applications onto vinyl substrates.			
		PL	ASTIC HOOK SHAPES
		AD	HESIVES & FRT TREATMENTS
VELCRO [®] Brand			AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE
Loop 3368 • Base material: Nylon		5	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
 Standard colors: Black, white Standard widths (inches): Up to 60 Standard put-ups: 50 yd rolls, 100 yd rolls 			
 Suggested mating component: Hook 845 Cycle life: Medium / Low 		SP	COLOR FASTNESS
Main applications Apparel, colostomy bags, sensor straps, materials handling, transportation interiors, moulding, cleaning products.			SHRINKAGE RESISTANCE
transportation interiors, moduling, cleaning products.			
			INTING OPTIONS BC CUSTOMIZED PRINTING
â îr 💞 🗘 🛅 🕏 🕿 🗶			
VELCRO® Brand		<u>co</u>	LORS
Loop 3905			HOOK 88 & LOOP 1000 COLOR CHART
 Base material: Nylon Standard colors: Black, white Standard widths (inches): Up to 58 			
 Standard put-ups: 100 yd rolls, 250 yd rolls Suggested mating component: Hook 830, Hook 847 Cycle life (Hook 830): Low 			
Main applications Apparel, surgical gowns, single use straps, packaging, moulding.			
Other applications requiring a product for limited number of uses.		AF	PPLICATIONS
			APPAREL CONSTRUCTION
Π💞 🔍 籠 🗧 🗶			
			PACKAGING PERSONAL CARE
AMERICAS PRODUCT LINE	VELCRO® and other marks are owned by Velcro Industries B.V.	© 2015	

Standard widths (inches): Up to 58
Standard put-ups: 500 yd rolls
Suggested mating component: Hook 805

VELCRO® Brand Loop 3707 • Base material: Nylon • Standard colors: Natural

Cycle life: Low
 Main applications



CHARACTERISTICS

TYPES O	FENGAGEMENT		
3	WOVEN HOOK & WOVEN LOOP	5	SELF-ENGAGING HOOK
	WOVEN MUSHROOM & LOOP/VELOUR	\bigcirc	SELF-ENGAGING HOOK & LC
90	PLASTIC HOOK & LOOP/VELOUR	NS	MAGNETIC ATTRACTION
****	PLASTIC HOOK & NONWOVEN LOOP		
PLASTIC	HOOK SHAPES		
00		00	
ADHESI	/ES & FRT TREATMENTS		
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE		AVAILABLE WITH F.R.T. TREA F.R.T. treatment (meets FAR 25.853, M
555	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD		
_			
SPECIAL	CHARACTERISTICS		
$\mathbf{\times}$	COLOR FASTNESS	<u>ک</u>	WEATHER RESISTANCE
	SHRINKAGE RESISTANCE		WASHABLE AT HIGH TEMPERATURES
PRINTIN	G OPTIONS		
ABC	CUSTOMIZED PRINTING		
COLORS			
H&L	HOOK 88 & LOOP 1000 COLOR CHART		AVAILABLE COLORS
APPLI	ICATIONS		
	IN TR		
,	APPAREL CONSTRUCTION	1	MEDICAL MILIT GOVER

VELCRO® Brand

- Base material: Nylon
- Standard colors: Black, white
- Standard widths (inches): Up to 58
- Standard put-ups: 100 yd rolls, 250 yd rolls
- Suggested mating component: Hook 830
- Cycle life: Low

Main applications

Apparel, surgical gowns, single use straps, packaging, moulding. Other applications requiring a product for limited number of uses.

Apparel, surgical gowns, single use straps, packaging, moulding. Other applications requiring a product for limited number of uses.

🗥 î 🚰 🛡 🎁 🗧 🖊



ABC



VELCRO® Brand

- Base material: Polyester
- Standard colors: White
- Standard widths (inches): Up to 54
- Standard put-ups: 500 yd rolls
- Suggested mating component: Hook 805
- Cycle life: Low

Main applications


Disposable apparel, surgical gowns, moulding, fabricated items. Other disposable applications.











TYPES OF ENGAGEMENT 9 5 WOVEN HOOK SELF-ENGAGING HOOK & WOVEN LOOP WOVEN MUSHROOM & LOOP/VELOUR \bigcirc SELF-ENGAGING HOOK & LOOP PLASTIC HOOK & LOOP/VELOUR S N S MAGNETIC ATTRACTION PLASTIC HOOK & NONWOVEN LOOP PLASTIC HOOK SHAPES 00 BURR 00 UNIDIRECTIONAL ADHESIVES & FRT TREATMENTS AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE * AVAILABLE WITH F.R.T. TREATMENT WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD 555 SPECIAL CHARACTERISTICS Ś COLOR FASTNESS WEATHER RESISTANCE H-WASHABLE AT HIGH TEMPERATURES SHRINKAGE RESISTANCE PRINTING OPTIONS ABC CUSTOMIZED PRINTING COLORS HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS H&L APPLICATIONS T۸ Ŷ





MILITARY &

<code>VELCRO®</code> and other marks are owned by <code>Velcro</code> Industries <code>B.V.</code> © 2015

TEXTILE HOOK & LOOP TAPES | LOOP | Nonwoven Loops

• Base material: Polypropylene, polyester

• Suggested mating component: Hook 819, Hook 847

• Standard widths (inches): 4, 120 • Standard put-ups: 4,000 yd rolls



CHARACTERISTICS

a a a b a b a b a b a b a b a a b a a b a a a a a a a a a a a a b a b a b a b a b a a b b b b b b b b b b b	OVEN HOOK WOVEN LOOP OVEN MUSHROOM LOOP/VELOUR LASTIC HOOK LOOP/VELOUR LASTIC HOOK NONWOVEN LOOP DOK SHAPES COC EXAMPS ALABLE WITH PRESSURE ENSITIVE ADHESIVE FELDABLE BY HEAT, SOLVENT R REACTIVATION METHOD	SELF-ENGAGING HOOK SELF-ENGAGING HOOK & LOOF MAGNETIC ATTRACTION
ADHESIVES SPECIAL CP SPECIAL CP	LOOP/VELOUR LASTIC HOOK LOOP/VELOUR LASTIC HOOK NONWOVEN LOOP DOK SHAPES	MAGNETIC ATTRACTION
ADHESIVES SPECIAL CF SPECIAL CF	LOOP/VELOUR LASTIC HOOK NONWOVEN LOOP DOK SHAPES	BURR UNIDIRECTION AVAILABLE WITH F.R.T. TREATM
ADHESIVES	NONWOVEN LOOP	AVAILABLE WITH F.R.T. TREATM
ADHESIVES ADHESI		AVAILABLE WITH F.R.T. TREATM
ADHESIVES ADHESIVES AD SI SI SPECIAL CF		AVAILABLE WITH F.R.T. TREATM
SPECIAL CH	VAILABLE WITH PRESSURE ENSITIVE ADHESIVE VELDABLE BY HEAT, SOLVENT	AVAILABLE WITH F.R.T. TREATM F.R.T. treatment (meets FAR 25.853, MVS
SISS W SPECIAL CH	ENSITIVE ADHESIVE ELDABLE BY HEAT, SOLVENT	AVAILABLE WITH F.R.T. TREATM F.R.T. treatment (meets FAR 25.853, MVS
SPECIAL CH		
	IARACTERISTICS	
	DLOR FASTNESS	WEATHER RESISTANCE
SI SI	HRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
PRINTING C	OPTIONS	
ABC C	USTOMIZED PRINTING	
COLORS		
	OOK 88 & LOOP 1000 DLOR CHART	AVAILABLE COLORS
APPLIC	ATIONS	
APF	PAREL CONSTRUCTION	MEDICAL MILITAR GOVERNM





Roofing / insulating membranes, surgical drapes and gowns,

VELCRO® Brand

VELCRO® Brand

• Standard colors: White

• Cycle life (Hook 819): Low

Main applications

baby diapers.

- Base material: Polypropylene
- Standard colors: White
- Standard widths (inches): 4, 120
- Standard put-ups: 4,000 yd rolls
- Suggested mating component: Hook 847
- Cycle life: Low

Main applications

Roofing / insulating membranes, surgical drapes and gowns, baby diapers.

Other disposable applications.





АВС

ABC



Plastic Hook Tapes





VELCRO® Brand		
Hook 704		TYPES OF ENGAGEMENT Image: Second State Sta
 Base material: Polyester / Without backing Standard colors: Black, white, natural 		& WOVEN LOOP
• Standard widths (inches): Up to 6		WOVEN MUSHROOM & LOOP/VELOUR SELF-ENGAGING HOOK & LOOP
Standard put-ups: 50 yd rolls Suggested mating component: Loop 9000		PLASTIC HOOK & LOOP/VELOUR MAGNETIC ATTRACTION
Cycle life: High / Medium		PLASTIC HOOK & NONWOVEN LOOP
Main applications Marine straps, outdoor.		
Other applications requiring UV resistance.		
		PLASTIC HOOK SHAPES

航 Tr 💞 💟 Tr 🗧 ቱ 🗶		
		ADHESIVES & FRT TREATMENTS
VELCRO® Brand		AVAILABLE WITH PRESSURE AVAILABLE WITH F.R.T. TREATMENT SENSITIVE ADHESIVE F.R.T. treatment (meets FAR 25.853, MVSS 302)
Hook 705		WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
 Base material: Nylon / Without backing Standard colors: Black, white, natural 		
• Standard widths (inches): Up to 6 • Standard put-ups: 50 yd rolls		
Suggested mating component: Loop 1000, Loop 3003 Cycle life: High (Loop 1000) / Medium (Loop 3003)		
Main applications		COLOR FASTNESS WEATHER RESISTANCE
Outerwear (jackets, ski pants), footwear, signage, straps.		SHRINKAGE RESISTANCE WASHABLE AT HIGH TEMPERATURES
		PRINTING OPTIONS
	888888888888888888888888888888888888888	ABC CUSTOMIZED PRINTING
VELCRO® Brand		COLORS
Hook 706		HALL COLOR CHART
 Base material: Nylon / Without backing Standard colors: Black, white, natural 		
 Standard widths (inches): Up to 6 Standard put-ups: 50 yd rolls 		
Suggested mating component: Loop 1000, Loop 2000 Cycle life: High / Medium		
Main applications		
Gaiters, backbelt support.		APPLICATIONS
Other applications requiring long cycle life and high shear strength.		
		APPAREL CONSTRUCTION MEDICAL MILITARY & GOVERNMENT
		PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES
AMERICAS PRODUCT LINE	VELCRO® and other marks are owned by Velcro Industries B.V. $\ensuremath{\mathbb{G}}$ 2015	


	Velcro [®]		
PLASTIC HOOK TAPES Shape 15		CHARACTERISTICS	
VELCRO® Brand Hook 711		TYPES OF ENGAGEMENT	
Base material: Polyethylene / Without backing		WOVEN HOOK & WOVEN LOOP	SELF-ENGAGING HOOK
 Standard colors: Black, white, natural Standard widths (inches): Up to 6 Standard put-ups: 25 yd rolls 		WOVEN MUSHROOM & LOOP/VELOUR	SELF-ENGAGING HOOK & LOOP
 Suggested mating component: Loop 3003, Loop 3200 Cycle life: Medium / Low 		PLASTIC HOOK & LOOP/VELOUR	N S MAGNETIC ATTRACTION
Main applications Surgical gowns, sterilizable and disposable goods.		PLASTIC HOOK & NONWOVEN LOOP	
		PLASTIC HOOK SHAPES	00 BURR UNIDIRECTIONAL
		ADHESIVES & FRT TREATMENTS	
VELCRO® Brand		AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE	AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
Hook 719		WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	
 Base material: Nylon / Without backing Standard colors: Black, coyote Standard widths (inches): Up to 6 			
 Standard put-ups: 25 yd rolls, 50 yd rolls Suggested mating component: Loop 1000, Loop 1100, Loop 4000, Loop 3368 			
Cycle life: High / Medium Main applications			WEATHER RESISTANCE
Apparel cuffs, military apparel, pouches and other equipment.		SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
		PRINTING OPTIONS	
		ABC CUSTOMIZED PRINTING	
VELCRO® Brand		COLORS	
Hook 745		HEL HOOK 88 & LOOP 1000 COLOR CHART	AVAILABLE COLORS
 Base material: Nylon / Without backing Standard colors: Black, natural, foliage green Standard widths (inches): Up to 6 			
Standard maths (inclus): Op to 0 Standard put-ups: 50 yd rolls Suggested mating component: High (Loop 1000) / Medium (Loop 3003)			
Cycle life: High / Medium Main applications			
Outwear, headgear, medical braces, fabricated items.		APPLICATIONS	
		AN TR	<u></u>
		APPAREL CONSTRUCTION	N MEDICAL MILITARY & GOVERNMENT
			🕿 🗱

AMERICAS PRODUCT LINE


SPECIALTIES

PACKAGING

PERSONAL CARE TRANSPORTATION



VELCRO® Brand



Velcro'

SPECIALTIES

PACKAGING

PERSONAL CARE

TRANSPORTATION

Standard colors: Black, white
Standard widths (inches): Up to 6
Standard put-ups: 50 yd rolls

Cycle life: Medium
 Main applications

• Base material: Polyethylene / Without backing


• Suggested mating component: Loop 3610, Loop 3905

Medical disposable, sterilizable goods, single use straps.

VELCRO[®] Brand Hook 811



	TYPES OF ENGAGEMENT
	WOVEN HOOK & WOVEN LOOP SELF-ENGAGING HOOK
	WOVEN MUSHROOM & LOOP/VELOUR SELF-ENGAGING HOOK & LOOP
	PLASTIC HOOK & LOOP/VELOUR MAGNETIC ATTRACTION
	PLASTIC HOOK & NONWOVEN LOOP
	PLASTIC HOOK SHAPES
	ADHESIVES & FRT TREATMENTS
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE
	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
	SPECIAL CHARACTERISTICS
	COLOR FASTNESS
	SHRINKAGE RESISTANCE WASHABLE AT HIGH TEMPERATURES
	PRINTING OPTIONS
	ABC CUSTOMIZED PRINTING
ABC	
222222222222222222222222222222222222222	COLORS
	HALL HOOK 88 & LOOP 1000 COLOR CHART
	APPLICATIONS
	APPAREL CONSTRUCTION MEDICAL MILITARY & GOVERNMENT
	PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES
VELCEDO® and other marks are exped by Valara Industrias $P_{\rm V} = 2015$	





PLASTIC HOOK TAPES | Shape 22



CHARACTERISTICS

VELCR0 [®] Brand		TYPES OF ENGAGEMENT	
Hook 886		WOVEN HOOK	SELF-ENGAGING HOOK
 Base material: Nylon / Backing: Polyester (Loop 3200) Standard colors: Black Standard widths (inches): 6-1/2, 13 Chandard and and and an 150 and antis 		& WOVEN LOOP	SELF-ENGAGING HOOK & LOOP
 Standard put-ups: 150 yd rolls Suggested mating component: Loop 3707 Cycle life: Low 		PLASTIC HOOK & LOOP/VELOUR	MAGNETIC ATTRACTION
Main applications Polishing discs.		PLASTIC HOOK & NONWOVEN LOOP	
		PLASTIC HOOK SHAPES	
		ADHESIVES & FRT TREATMENTS	
		AVAILABLE WITH PRESSURE	AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302
VELCRO® Brand Hook 887		SENSITIVE ADHESIVE	F.R.T. treatment (meets FAR 25.853, MVSS 302
Base material: Polypropylene / Backing: Polyester (Loop 3200)		WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	
 Standard colors: Black Standard widths (inches): 12-3/8, 14 			
Standard put-ups: 150 yd rolls Suggested mating component: Loop 3707		SPECIAL CHARACTERISTICS	
• Cycle life: Low		COLOR FASTNESS	weather resistance
Main applications Polishing discs.		SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
		ABC CUSTOMIZED PRINTING	
		201.000	
			AVAILABLE COLORS
		HOOK 88 & LOOP 1000 COLOR CHART	AVAILABLE COLORS



PACKAGING



TRANSPORTATION

PERSONAL CARE

SPECIALTIES

PLASTIC HOOK TAPES | Shape 24

VELCRO® Brand Hook 733

- Base material: Polyethylene / Without backing
- Standard colors: Black
- Standard widths (inches): 4-7/32 (107mm)
- Standard put-ups: 97 yd (90m) rolls
- Suggested mating component: Loop 1000, Loop 3003, Loop 3001
- Cycle life (Loop 001): Medium

Main applications

Photovoltaic panels, outdoor applications.

Other applications requiring high strength performance, waterproof and UV resistance.



Velcro*

PACKAGING

PERSONAL CARE

TRANSPORTATION



VELCRO® Brand Hook 752

- Base material: Polypropylene / Without backing
- Standard colors: Silver
- Standard widths (inches): Up to 6
- Standard put-ups: 25 yd rolls
- Suggested mating component: Loop 9000 Polyester
- Cycle life: Low

Main applications

Solar panels.





VELCRO® Brand Hook 757

- Base material: Nylon / Without backing
- Standard colors: Black
- Standard widths (inches): Up to 6
- Standard put-ups: 25 yd rolls
- Suggested mating component: Loop 1000, Loop 3001 • Cycle life: Low
- oyere mer Low

Main applications

RV panels, holding scrubbing pad. Other applications requiring high peel performance.








ADHESIVES & FRT TREATMENTS	TYPES OF E	NGAGEMENT		
A LOOP/VELOUR PLASTIC HOOK PLASTIC HOOK R LOOP/VELOUR PLASTIC HOOK PLASTIC HOOK SHAPES PLASTIC HOOK SHAPES <td></td> <td></td> <td>6</td> <td>SELF-ENGAGING HOOK</td>			6	SELF-ENGAGING HOOK
A LOOP/VELOUR PLASTIC HOOK SHAPES PLASTIC HOOK SHAPES			\bigcirc	SELF-ENGAGING HOOK & LOOP
Image: Plastic Hook Shapes			NS	MAGNETIC ATTRACTION
OO				
ADHESIVES & FRT TREATMENTS AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD SPECIAL CHARACTERISTICS COLOR FASTNESS SHRINKAGE RESISTANCE WINDERCETIONS PINTING OPTIONS CUSTOMIZED PRINTING COLORS MOK 88 & LOOP 1000	PLASTIC HO	DOK SHAPES		
AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE AVAILABLE WITH F.R.T. TREATMEN Image: Sensitive Adhesive F.R.T. treatment (meets FAR 25.853, MVSS 30 Image: Sensitive Adhesive WELDABLE BY HEAT, SOLVENT Image: Sensitive Adhesive Image: Sensitive Adhesive Image: Sensitive Adhesive Image: Sensitiv	00		00	
SENSITIVE ADHESIVE SENSITIVE ADHESIVE FR.T. treatment (meets FAR 25:853, MVSS 30 SPECIAL CHARACTERISTICS COLOR FASTNESS SHRINKAGE RESISTANCE WASHABLE AT HIGH PRINTING OPTIONS ABC CUSTOMIZED PRINTING HOOK 88 & LOOP 1000 FR.T. treatment (meets FAR 25:853, MVSS 30	ADHESIVES	& FRT TREATMENTS		
SPECIAL CHARACTERISTICS SPECIAL CHARACTERISTICS COLOR FASTNESS COLOR FASTNESS SHRINKAGE RESISTANCE SHRINKAGE RESISTANCE COLORS COLORS COLORS AUXILABLE COLORS AVAILABLE COLORS AVAILABLE COLORS				AVAILABLE WITH F.R.T. TREATMEN F.R.T. treatment (meets FAR 25.853, MVSS 30
COLOR FASTNESS COLOR FASTNESS WEATHER RESISTANCE WASHABLE AT HIGH TEMPERATURES WASHABLE AT HIGH TEMPERATURES WASHABLE AT HIGH TEMPERATURES COLORS COLORS HOOK 88 & LOOP 1000 WAILABLE COLORS				
SHRINKAGE RESISTANCE WASHABLE AT HIGH PRINTING OPTIONS ABC CUSTOMIZED PRINTING COLORS HOOK 88 & LOOP 1000 ABC ABC CUSTOMIZED PRINTING	SPECIAL CH	IARACTERISTICS		
	CC	DLOR FASTNESS	Č.	WEATHER RESISTANCE
ABC CUSTOMIZED PRINTING	SI SI	HRINKAGE RESISTANCE		
ABC CUSTOMIZED PRINTING COLORS HOOK 88 & LOOP 1000	PRINTING C	PPTIONS		
HOOK 88 & LOOP 1000		USTOMIZED PRINTING		
HOOK 88 & LOOP 1000 COLOR CHART	COLORS			
				AVAILABLE COLORS
	APPLIC	ATIONS		

SPECIALTIES




AMERICAS PRODUCT LINE

PLASTIC	HOOK	TAPES	I	Shape	66
---------	------	-------	---	-------	----





VELCRO® Brand Hook 5111 Base material: Nylon / Without backing Standard colors: Black Standard widths (inches): 1 Standard put-ups: 25 yd rolls Suggested mating component: Loop 1000 Cycle life: Medium / Low Main applications Transportation interiors.	TYPES OF ENGAGEMENT WOVEN HOOK & WOVEN LOOP WOVEN MUSHROOM & LOOPVELOUR WOVEN MUSHROOM & LOOPVELOUR PLASTIC HOOK & NONWOVEN LOOP PLASTIC HOOK & NONWOVEN LOOP PLASTIC HOOK & NONWOVEN LOOP PLASTIC HOOK & NONWOVEN LOOP
	ADHESIVES & FRT TREATMENTS
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE Image: Construction of the sense
	COLOR FASTNESS SHRINKAGE RESISTANCE PRINTING OPTIONS
	ABC CUSTOMIZED PRINTING
	HEL HOOK 88 & LOOP 1000 COLOR CHART
	APPLICATIONS
F	APPAREL CONSTRUCTION MEDICAL MILITARY & GOVERNMENT
	PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES



AMERICAS PRODUCT LINE

VELCRO® and other marks are owned by Velcro Industries B.V. © 2015





Velcro*

CHARACTERISTICS

TIFESC	OF ENGAGEMENT		
6	WOVEN HOOK & WOVEN LOOP	5	SELF-ENGAGING HOOK
	WOVEN MUSHROOM & LOOP/VELOUR	0	SELF-ENGAGING HOOK & LOOP
9	PLASTIC HOOK & LOOP/VELOUR	NS	MAGNETIC ATTRACTION
	PLASTIC HOOK & NONWOVEN LOOP		
PLASTIC	HOOK SHAPES		
00		00	
ADHESI	VES & FRT TREATMENTS		
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE		AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
555	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD		
SPECIAL	CHARACTERISTICS		
$\mathbf{\times}$	COLOR FASTNESS		WEATHER RESISTANCE
×	SHRINKAGE RESISTANCE		WASHABLE AT HIGH TEMPERATURES
	IG OPTIONS		_
ABC	CUSTOMIZED PRINTING		
COLORS			
H&L	. HOOK 88 & LOOP 1000 COLOR CHART		AVAILABLE COLORS
APPL	ICATIONS		
			$\overline{\mathbf{v}}$

PERSONAL CARE


TRANSPORTATION

SPECIALTIES



VELCRO® Brand


Self-engaging Hook & Loop Tapes







VELCRO® Brand Double Face 200	* * * * MADE * * IN EU * * * *		TYPES OF ENGAGEMENT	
 Base material: Nylon Standard colors: Black, white Standard widths (inches): 63/64 (25mm), 1-37/64 (40mm) Standard put-ups: 27 yd (25m) rolls Suggested mating component: Self-engaging Cycle life: Medium 		Backside	WOVEN HOOK & WOVEN LOOP WOVEN MUSHROOM & LOOP/VELOUR PLASTIC HOOK & LOOP/VELOUR	SELF-ENGAGING HOOK & LOOP
Main applications Cable management, orthopedics, automotive accesories, bundling, sports. Other applications requiring a high temperature, chemical resistance or no product delamination.			PLASTIC HOOK & NONWOVEN LOOP	00 BURR UNIDIRECTIONAL
<u>í î i i i x</u>			ADHESIVES & FRT TREATMENTS	
VELCRO® Brand Back to back Hoop & Loop • Base material: Nylon • Standard colors: Black			AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE	ER.I. treatment (meets FAR 25.853, MVSS 302)
 Standard widths (inches): 1, 1-1/2, 2 Standard put-ups: 25 yd rolls Suggested mating component: Self-engaging Cycle life: High 		Backside	COLOR FASTNESS	weather resistance
Main applications Cable management, orthopedics, sports, straps, umbrellas. Other applications requiring high cycle life and flexibility.			SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
â îr 💕 🗘 18 🗧 🗶			ABC CUSTOMIZED PRINTING	
VELCRO® Brand ONE-WRAP®			COLORS HOOK 88 & LOOP 1000 COLOR CHART	Available colors
 Base material: Polypropylene (Hook) / Backing: Nylon (Loop 3610) Standard colors: Black, white, adamia, bacardi brown, beige, coachman green, lemon, light grey, orange, red, royal blue Standard widths (inches): 3/8, 1/2, 5/8, 3/4, 1, 1-1/2, 2, 3, 4 Standard put-ups: 25 yd rolls, 150 yd rolls, 200 yd rolls Suggested mating component: Self-engaging Cycle life: Medium 				
Main applications Cable management, medical equipment bundling, materials handling, gardening, sports and leisure activities equipment. Other applications requiring a strong, durable, adjustable and reusable self-engaging fastener.		Backside	APPLICATIONS	<u> </u>
â îi 💕 💙 🛅 🗧 🗱			APPAREL CONSTRUCTIO	GOVERNMENT



🚺 VELCRO

APPARFI

PACKAGING

CONSTRUCTION


PERSONAL CARE


MEDICAL

TRANSPORTATION

MILITARY & GOVERNMENT


SPECIALTIES







VELCRO® Brand Specialties



















CHARACTERISTICS



	Sec. 1997	Velcro*	
SPECIALTIES PACKAGING Flexible Packaging			CHARACTERISTICS
VELCRO® Brand PRESS-LOK® 775 • Base material: Polyethylene • Standard colors: Natural • Standard widths (inches): 1-1/4 • Standard put-ups: 6000 ft spool • Suggested mating component: Self-engaging • Cycle life: Medium Main applications			TYPES OF ENGAGEMENT Image: Section of the sect
Food and non-food flexible packaging, to be welded onto PE films.			PLASTIC HOOK SHAPES
VELCRO® Brand PRESS-LOK® 776 • Base material: Polyethylene • Standard colors: Natural • Standard widths (inches): 1-1/4 • Standard put-ups: 4000 ft spool • Suggested mating component: Self-engaging • Cycle life: Medium			ADHESIVES & FRT TREATMENTS AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE Image: Structure of the sensitive adhesive of the sense adhesis adhesive of the sensitive adhesive of the sen
Main applications Ideal for powder products, food and non-food flexible packaging, to be welded on PE films. Image: Image			SPECIAL CHARACTERISTICS Color Fastness Image: Color Fastness Image: Shrinkage resistance Image: Color Fastness Image: Shrinkage resistance Image: Color Fastness
VELCRO® Brand PRESS-LOK® 779 • Base material: Polyethylene • Standard colors: Natural • Standard widths (inches): 7/8 • Standard put-ups: 7000 ft spool • Suggested mating component: Self-engaging • Cycle life: Medium			ABC CUSTOMIZED PRINTING COLORS Image: Hook 88 & LOOP 1000 COLOR CHART
Main applications Ideal for powder products, food and non-food flexible packaging, to be welded on PE films. Image: Application of the state			
			APPLICATIONS

*

SPECIALTIES

PERSONAL CARE TRANSPORTATION

1T

PACKAGING

 $\mathbf{\overline{\mathbf{v}}}$

SPECIALTIES PACKAGING Flexible Packaging			CHARACTERISTICS	
VELCRO® Brand PRESS-LOK® 731 (Adhesive 9932) • Base material: Polypropylene / With or without PS A backing • Standard colors: Natural • Standard widths (inches): Up to 6 • Standard put-ups: 50yd rolls • Suggested mating components: Self-engaging • Cycle life: Medium Main applications Medical pouches, stationery, promotional gift.			TYPES OF ENGAGEMENT WOVEN HOOK & WOVEN LOOP WOVEN MUSHROOM & LOOPVELOUR WOVEN MUSHROOM & LOOPVELOUR PLASTIC HOOK & LOOPVELOUR WEXTIC HOOK & NONWOVEN LOOP	SELF-ENGAGING HOOK SELF-ENGAGING HOOK & LOOP
			PLASTIC HOOK SHAPES	00 BURR UNIDIRECTIONAL
VELCRO® Brand Touch & Seal Closure (Weldable) Hook 832 / Velour 3314 • Base material: Polyethylene (Hook 832), nylon (Loop 3314) • Standard colors: Natural • Standard widths (inches): 3/8 • Standard put-ups: Spools • Suggested mating components: NA • Cycle life: Low			ADHESIVES & FRT TREATMENTS AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE SSS WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	EXAMPLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
Main applications Bags, closure to be welded onto PE films for non-food applications. Image: A state of the state	29		SPECIAL CHARACTERISTICS Color fastness SHRINKAGE RESISTANCE	Weather resistance
			PRINTING OPTIONS	
			COLORS	AVAILABLE COLORS
		-	APPLICATIONS	
			APPAREL CONSTRUCTION	DN MEDICAL MILITARY & GOVERNMENT

SPECIALTIES

TRANSPORTATION


PACKAGING

PERSONAL CARE



CHARACTERISTICS

 VELCRO® Brand Hook 701 Base material: Polypropylene (Hook) / Backing: Polypropylene (Nonwoven) Standard colors: Natural Standard widths (mm): 90 (2x15 Hook lanes) Standard put-ups: 1,400m rolls Suggested mating components: Loop 3905, FNL 264 Cycle life (Loop 3905): Low Main applications Baby and adult diapers. Other applications requiring hook integrated into nonwoven materials. 	TYPES OF ENGAGEMENTImage: State in the image in th	SELF-ENGAGING HOOK SELF-ENGAGING HOOK & LOOP MAGNETIC ATTRACTION
	ADHESIVES & FRT TREATMENTS Image: Second S	
	PRINTING OPTIONS ABC CUSTOMIZED PRINTING COLORS Image: Door of the state of th	AVAILABLE COLORS
	APPAREL CONSTRUCT APPAREL CONSTRUCT PACKAGING PERSONAL O	







CHARACTERISTICS

VELCRO® Brand MIGG 15-1 • Base material: Nylon (Hook) / polyurethane (gasket) • Standard colors: Black / grey • Standard widths (mm): 15 • Standard put-ups: Bulk pieces • Suggested mating components: Loop Auto MIGG, Loop Auto Standard • Cycle life: Medium Main applications	Carrier	TYPES OF ENGAGEMENT WOVEN HOOK & WOVEN LOOP WOVEN MUSHROOI & LOOP/VELOUR PLASTIC HOOK & NONWOVEN LOOP
Seat hook tie down.		PLASTIC HOOK SHAPES
VELCRO® Brand HF3 • Base material: Nylon (Hook) / polyurethane (gasket) • Standard colors: Black / blue • Standard widths (mm): 12, 15 • Standard put-ups: Bulk pieces • Suggested mating components: Loop Auto MIGG • Cycle life: Medium / Low		ADHESIVES & FRT TREATMEN AVAILABLE WITH P SENSITIVE ADHESI SSS WELDABLE BY HEA OR REACTIVATION
Main applications Automotive seating.		SPECIAL CHARACTERISTICS
		COLOR FASTNESS
VELCRO® Brand Flex-MIGG • Base material: Nylon (Hook) / polyurethane (gasket) • Standard colors: Black / blue, black / green • Standard widths (mm): 12, 15 • Standard put-ups: Bulk pieces • Suggested mating components: Loop Auto MIGG • Cycle life: Low		PRINTING OPTIONS
Main applications Automotive seating.		H&L HOOK 88 & LOOP I COLOR CHART
ÎX 🖓 🗘 îE 🗦 🕿 米		
		APPLICATIONS

0 SELF-ENGAGING HOOK & LOOP N S MAGNETIC ATTRACTION 00 BURR 00 UNIDIRECTIONAL NTS X PRESSURE AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302) AT, SOLVENT METHOD Č, WEATHER RESISTANCE WASHABLE AT HIGH TEMPERATURES TANCE 31 31 TIN NS AVAILABLE COLORS 1000 **I**X •¥ Â $|\bigcirc$

MEDICAL

 \mathbf{C}

TRANSPORTATION

APPAREL

ÎΠ

PACKAGING

CONSTRUCTION

PERSONAL CARE

MILITARY & GOVERNMENT

*

SPECIALTIES

5

SELF-ENGAGING HOOK



CHARACTERISTICS

Î

PACKAGING

5

PERSONAL CARE

TRANSPORTATION

*

SPECIALTIES

SFECIALITES T TRANSPORTATION T Seating Loops		 CHARACTERISTICS
VELCRO® Brand LOOP Auto Standard 9 Base material: Nylon 9 Standard colors: Natural 9 Standard widths (mm): 33, 39 9 Standard put-ups: Spools 9 Suggested mating components: DCS 36, MIGG 15, MIGG 15-1 9 Cycle life: Medium Main applications Seat loop tie down.		TYPES OF ENGAGEMENT WOVEN HOOK & WOVEN LOOP WOVEN MUSHROOM & LOOP/VELOUR WOVEN MUSHROOM & LOOP/VELOUR PLASTIC HOOK & LOOP/VELOUR
Îa ở ♥ 16 ‡ ≈ *		PLASTIC HOOK SHAPES
VELCRO® Brand LOOP Auto MIGG Base material: Polyester Standard colors: Natural Standard widths (mm): 40 Standard put-ups: Spools Suggested mating components: MIGG 15, MIGG 15-1, HF3, Flex-MIGG, 4Gi Cycle life: Medium		ADHESIVES & FRT TREATMENTS AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE Statistic Control of the sensitive adhesive Stati
Main applications Automotive seating.	G	SPECIAL CHARACTERISTICS COLOR FASTNESS WEATHER RESISTANCE SHRINKAGE RESISTANCE WASHABLE AT HIGH TEMPERATURES
		 ABC CUSTOMIZED PRINTING
		COLORS HAL HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS
		APPLICATIONS Image: Apparel Image: A



CHARACTERISTICS

6	WOVEN HOOK & WOVEN LOOP		6	SELF-ENGAGING	НООК
	WOVEN MUSHRO & LOOP/VELOUR		0	SELF-ENGAGING	HOOK & LOOP
9	PLASTIC HOOK & LOOP/VELOUR		NS	MAGNETIC ATTR	ACTION
	PLASTIC HOOK & NONWOVEN LO	DOP			
PLASTIC	HOOK SHAPES				
00			00	BURR	UNIDIRECTION
ADHESI	VES & FRT TREATM	MENTS			
	AVAILABLE WITH SENSITIVE ADHI	I PRESSURE ESIVE		AVAILABLE WITH F.R.T. treatment (meet	F.R.T. TREATMEN s FAR 25.853, MVSS 3
555	WELDABLE BY H OR REACTIVATIO	IEAT, SOLVENT IN METHOD			
SPECIAL	. CHARACTERISTIC	cs			
	COLOR FASTNES		Č.	WEATHER RESIS	TANCE
×	SHRINKAGE RES	SISTANCE		WASHABLE AT H TEMPERATURES	
PRINTIN	ig options				
ABC	CUSTOMIZED PF	RINTING			
	. HOOK 88 & LOO	P 1000		AVAILABL	
H&L	COLOR CHART	1000		AVAILABL	ECULORS
APPL	ICATIONS				
		T			\bigcirc
	APPAREL	CONSTRUCTIO	N	MEDICAL	MILITARY GOVERNME

PECIALTIES TRANSPORTATION Interior Parts	
VELCRO® Brand Burr Hook • Base material: Nylon • Standard colors: Black • Standard widths (mm): 50 • Standard put-ups: Bulk pieces • Suggested mating components: Cut loop carpets • Cycle life: High	
Main applications Carpet fixation.	




BURR



VELCRO[®] Brand

Converted Products



CONVERTED PRODUCTS | SHAPES

• Standard colors: Black, white

• Standard put-ups: 25 yd rolls

VELCRO® Brand **VELCOIN®**

• Cycle life: High Main applications



CHARACTERISTICS

6	WOVEN HOOK & WOVEN LOOP	5	SELF-ENGAGING HOOK
	WOVEN MUSHROOM & LOOP/VELOUR	0	SELF-ENGAGING HOOK & LOOP
90	PLASTIC HOOK & LOOP/VELOUR	NS	MAGNETIC ATTRACTION
	PLASTIC HOOK & NONWOVEN LOOP		
PLASTIC	HOOK SHAPES		
00		00	
ADHESIV	ES & FRT TREATMENTS		
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE		AVAILABLE WITH F.R.T. TREATMEN F.R.T. treatment (meets FAR 25.853, MVSS 30
555	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD		
SPECIAL	CHARACTERISTICS		
$\mathbf{\times}$	COLOR FASTNESS		WEATHER RESISTANCE
×	SHRINKAGE RESISTANCE		WASHABLE AT HIGH TEMPERATURES
PRINTIN	G OPTIONS		
ABC	CUSTOMIZED PRINTING		
COLORS			
Hal	HOOK 88 & LOOP 1000 COLOR CHART		AVAILABLE COLORS
APPLI	CATIONS		
			<u> </u>



555

• Base material: Nylon (Hook 88 & Loop 1000)

• Standard widths (inches): 3/8, 1/2, 5/8, 3/4, 7/8, 1-3/8, 1-7/8

Apparel, office folders, stationery, rigid packaging & trays.

Straps

Hook 088 / Loop 001

- Base material: Nylon / polyester
- Standard colors: Hook 88 & Loop 1000 colour chart
- Standard widths (inches): 1/2, 5/8, 3/4, 1, 1-1/2, 2, 4, 6
- Standard put-ups: In bulk, customized
- Suggested mating components: Self-engaging
- Cycle life: High



Main applications

Cable management, tourniquet straps, packaging, metallic trolley closure, automotive accessories (trunk), sports.

Custom manufactured including ultrasonic welding and stitching.





WOVEN MUSHROOM & LOOP/VELOUR \bigcirc PLASTIC HOOK & LOOP/VELOUR NS



SELF-ENGAGING HOOK

SELF-ENGAGING HOOK & LOOP

AVAILABLE WITH F.R.T. TREATMENT



ADHESIVES & FRT TREATMENTS

AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE

WOVEN HOOK

& WOVEN LOOP

CHARACTERISTICS

TYPES OF ENGAGEMENT

3

Gr



*

5

VELCRO[®] Brand **VELSTRAP®**



VELCRO[®] Brand **Facestrap**

and the second second second second	and the second second	State of the state of the	State of the local division of the	HEARING MERINA	Statistical Property in the
and the second			A STATE		
			1. 我们想要到1. 任日		
			ALC: NO DECISION OF THE		
					기 이 동물을 사실했
			Contraction of the		
			10000		

VELCRO[®] Brand **Backstrap**

Contraction of the lot	AN OL STREET, SPACE	No. of Concession, Name	STATISTICS IN CONTRACTOR
		A DATE OF A	

WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD 555 SPECIAL CHARACTERISTICS ģ COLOR FASTNESS WEATHER RESISTANCE H-WASHABLE AT HIGH TEMPERATURES SHRINKAGE RESISTANCE PRINTING OPTIONS ABC CUSTOMIZED PRINTING COLORS HOOK 88 & LOOP 1000 COLOR CHART AVAILABLE COLORS H&L

APPLICATIONS



CHARACTERISTICS

TYPES OF ENGAGEMENT

WOVEN HOOK

3

CONVERTED PRODUCTS | STRAPS

VELCRO[®] Brand **ONE-WRAP®** Strap

- Base material: Polypropylene (Hook) / Backing: Nylon (Loop 3610) • Standard colors: Black, white, adamia, bacardi brown, beige,
- coachman green, lemon, light grey, orange, red, royal blue
- Standard sizes (inches): *
- Standard put-ups:
- Suggested mating component: Self-engaging
- Cycle life: Medium



VELCRO[®] Brand **ONE-WRAP®** Strap Fire Retardant

- Base material: Polypropylene (Hook) / Backing: Nylon (Loop 3610)
- Standard colors: Black, cranberry
- Standard sizes (inches): *
- Standard put-ups: *
- Suggested mating components: Self-engaging
- Cycle life: Medium

(*)

|--|--|--|--|--|--|--|

Main applications

Cable management, medical equipment bundling, materials handling, gardening, sports and leisure activities equipment. Other applications requiring a strong, durable, adjustable and reusable self-engaging fastener.



 -			_	

Main applications

Cable management, materials handling, adjustable straps. Other applications requiring a fire retardant self-engaging fastener.

22 ABC




	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE	AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302
555	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	
SPECIAL	CHARACTERISTICS	
\mathbf{X}	COLOR FASTNESS	WEATHER RESISTANCE
×	SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
	G OPTIONS	
HEL	HOOK 88 & LOOP 1000 COLOR CHART	AVAILABLE COLORS

SIZES	STRAPS / SPOOL	STRAP SHAPE
1/2" x 8"	1329	0
3/4" x 5"	1440	
3/4" x 6"	1200	D
3/4" x 8"	900	
3/4" x 12"	600	₽
3/4" x 18"	400	
1" x 8"	675	
1" x 12"	450	
1/2" x 10"	1170	

PUT-UP


1 3/4" x 23 1/2"



1

230

HOW TO USE IT





5

SELF-ENGAGING HOOK

APPLICATIONS

PACKAGING



PERSONAL CARE



MILITARY & GOVERNMENT

SPECIALTIES



VELCRO® Brand QWIK-TIE Strap

- Base material: Polypropylene (Hook) / Backing: Nylon (Loop 3905)
- Standard colors: Black, white, grey / black, red / black
- Standard sizes (inches): *
- Standard put-ups: *
- Suggested mating component: Self-engaging
- Cycle life: Medium / Low

	*	
--	---	--

Main applications

Cable management, medical equipment bundling, materials handling, gardening, sports and leisure activities equipment. Other applications requiring a strong, durable, adjustable and reusable self-engaging fastener.







(*)

()			
	SIZES	STRAPS / SPOOL	STRAP SHAPE
3	/4" x 5"	1440	
3	/4" x 6"	1200	
3	/4" x 8"	900	
3/	/4" x 12"	600	₽
	1" x 8"	675	
1	l" x 12"	450	

PUT-UP









CHARA	CTERISTICS		
TYPES OF	ENGAGEMENT		
	WOVEN HOOK & WOVEN LOOP	5	SELF-ENGAGING HOOK
	WOVEN MUSHROOM & LOOP/VELOUR	\bigcirc	SELF-ENGAGING HOOK & LOOP
	PLASTIC HOOK & LOOP/VELOUR	NS	MAGNETIC ATTRACTION
	PLASTIC HOOK & NONWOVEN LOOP		
PLASTIC H	100K SHAPES		
00		00	BURR UNIDIRECTIONAL
ADHESIVE	S & FRT TREATMENTS		
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE		AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD		
SPECIAL C	CHARACTERISTICS		
	COLOR FASTNESS	Č.	WEATHER RESISTANCE
	SHRINKAGE RESISTANCE		WASHABLE AT HIGH TEMPERATURES
PRINTING	OPTIONS		
ABC	CUSTOMIZED PRINTING		
COLORS			
	HOOK 88 & LOOP 1000 COLOR CHART		AVAILABLE COLORS
APPLIC	CATIONS		



AMERICAS PRODUCT LINE

CONVERTED PRODUCTS | STRAPS





Buckle supplement

- Base material: Polyamide 12 (Hook 805)
- Standard colours: Black
- Standard widths (mm): 25, 38, 50
- Standard put-ups: Bulk pieces
- Suggested mating component: Velour 3165
- Cycle life: Medium






VELCRO® Brand Back to Back Velour 3165

- Base material: Polyamide
- Standard colours: Black, white
- Standard widths (mm): 20, 25, 30, 38, 50, 1300
- Standard put-ups: 25m rolls
- Suggested mating components: Hook 088, Hook 805
 Cycle life (Hook 805): Medium





AMERICAS PRODUCT LINE

VELCRO® and other marks are owned by Velcro Industries B.V. © 2015

HOW TO USE IT			
	2	3	4

Hook tip

- Base material: Polyamide (Hook 805)
- Standard colours: Black
- Standard widths (mm): 25, 38, 50
- Standard put-ups: Bulk pieces
- Suggested mating component: Velour 3165





CHARACTERISTICS	
TYPES OF ENGAGEMENT	
WOVEN HOOK & WOVEN LOOP	SELF-ENGAGING HOOK
WOVEN MUSHROOM & LOOP/VELOUR	SELF-ENGAGING HOOK & LOOP
PLASTIC HOOK & LOOP/VELOUR	MAGNETIC ATTRACTION
PLASTIC HOOK & NONWOVEN LOOP	
PLASTIC HOOK SHAPES	
ADHESIVES & FRT TREATMENTS	
AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE	AVAILABLE WITH F.R.T. TREATMENT F.R.T. treatment (meets FAR 25.853, MVSS 302)
WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD	
SPECIAL CHARACTERISTICS	
COLOR FASTNESS	WEATHER RESISTANCE
SHRINKAGE RESISTANCE	WASHABLE AT HIGH TEMPERATURES
PRINTING OPTIONS	
ABC CUSTOMIZED PRINTING	
COLORS	
HEL HOOK 88 & LOOP 1000 COLOR CHART	AVAILABLE COLORS

APPLICATIONS



 \bigcirc

NS

00

*

ģ

H-

BURR

SELF-ENGAGING HOOK

MAGNETIC ATTRACTION

SELF-ENGAGING HOOK & LOOP

-

AVAILABLE WITH F.R.T. TREATMENT

WEATHER RESISTANCE

WASHABLE AT HIGH TEMPERATURES

AVAILABLE COLORS

Ŷ

MEDICAL

TRANSPORTATION


MILITARY & GOVERNMENT

җ


SPECIALTIES

UNIDIRECTIONAL

CONVERTED PRODUCTS | STRAPS



CONVERTED PRODUCTS | LAMINATES



CHARACTERISTICS

H-

SHRINKAGE RESISTANCE

CUSTOMIZED PRINTING

HOOK 88 & LOOP 1000 COLOR CHART

T٨

CONSTRUCTION

 $\mathbf{\overline{\mathbf{S}}}$

PERSONAL CARE

Ý

MEDICAL

TRANSPORTATION

MILITARY & GOVERNMENT

⋇

SPECIALTIES

PRINTING OPTIONS

ABC

COLORS

H&L

APPLICATIONS

APPARFI

PACKAGING

WASHABLE AT HIGH TEMPERATURES

AVAILABLE COLORS



VELCRO® Brand


VELCRO[®] Brand

Self-Engaging PRESS-LOK[®] Hook

• Base material: Polyethylene / Without backing • Suggested mating component: Self-engaging

CHARACTERISTICS

	TYPES OF ENGAGEMENT
	WOVEN HOOK & WOVEN LOOP
	WOVEN MUSHROOM & LOOP/VELOUR SELF-ENGAGING HOOK & LOOP
	PLASTIC HOOK & MAGNETIC ATTRACTION
	PLASTIC HOOK & NONWOVEN LOOP
	PLASTIC HOOK SHAPES
	ADHESIVES & FRT TREATMENTS
	AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE
	WELDABLE BY HEAT, SOLVENT OR REACTIVATION METHOD
	SPECIAL CHARACTERISTICS
	COLOR FASTNESS
	SHRINKAGE RESISTANCE WASHABLE AT HIGH
	PRINTING OPTIONS
	ABC CUSTOMIZED PRINTING
	COLORS
	HALL HOOK 88 & LOOP 1000 COLOR CHART
	APPLICATIONS
	APPAREL CONSTRUCTION MEDICAL MILITARY &
-	
and the second division of the second divisio	PACKAGING PERSONAL CARE TRANSPORTATION SPECIALTIES





Complementary information







WOVEN HOOK 88 & LOOP 1000







STANDARD COLORS





NOTE: Please note that all color pictures and RAL codes are for reference only. The colors are defined under Illuminant D65 and its specification is max CMC dE 2.



Shapes

PLASTIC TAPES ARE ENGINEERED MOLDED HOOK SHAPES DESIGNED FOR SUPERIOR PERFORMANCE CHARACTERISTICS WITH A WIDE VARIETY OF WOVEN, KNITTED OR NONWOVEN LOOP TAPES





NOTE: For further information, please see VELCRO® Brand Plastic Hook Tapes brochure.



Semipermanent

Pressure Sensitive Adhesives

PRESSURE SENSITIVE ADHESIVES ARE POPULAR BECAUSE OF THEIR EASE OF APPLICATION - SIMPLY REMOVE THE RELEASE LINER AND PRESS THE TAPE IN PLACE


Application method



Permanent

Heat or Solvent Activated Adhesives


HEAT AND SOLVENT ACTIVATED ADHESIVES PROVIDE THE STRONGEST BOND TO THE TAPE ITSELF AND CAN BE MADE READY FOR INSTANT BONDING BY MANY METHODS OF APPLICATION



* Meets FAR 25.853 with FR textile.

** Meets BMS 8-285 with FR textile.











		JOINTS	
	Automated		
	 Sewing area: We have different patterns, it depends of the product design Materials: Different materials Resistance: Multiple combinations 	50x100mm	-
	Walking feet		
SEWING	 Sewing area: pending Materials: pending Resistance: pending 	50x100mm	
	Cross box stitch		
	Sewing area:	50x100mm	٦
	 This cross box stitch depends of the width of the materials and also of the overlap of the materials Materials: Multiple combinations Resistance: Multiple combinations 		



PRINTING METHODS	Type of printing	Standard Colors	Standard Materials	Standard Length / Area	Printing width	A (
FLEXOGRAPHIC PRINTING	Continuous	10 color	On back side of woven tapes. On knitted tapes	Continuous length	Up to 14-3/4"	
S ve	elcr	0.	5	velc	RO	
PAD PRINTING	Single printing of bulk pieces	One or two colors	On back side of woven tapes. On knitted tapes	2-3/4" x 5-1/2"	-	-
	í	S v	elcr	0°		Resolution
STATIONARY SCREEN PRINTING	Single printing of bulk pieces	One color	On back side of woven tapes. On knitted tapes	14 x 14" to 28 x 38"	-	Doc
HEAT TRANSFER	Single printing of bulk pieces	Multiple colors	On back side of woven tapes. On knitted tapes	6 x 12" maximum image transfer	-	
	0	ve	LCRO			• (

NOTE: Please take that printed samples are for reference only. Pad printing sample has been made with two cycles.



PRINTING METHODS	Type of printing	Standard Colors	Standard Materials	Standard Length / Area	Printing width	▲ ⊖
ROTARY SCREEN	Continuous	16 color	On knitted tapes	Continuous length	Up to 60"	_
						Resolution
DYE SUBLIMATION	Continuous	Digital artwork	On knitted tapes	Continuous length	Up to 60"	
						♥ 🕂

NOTE: Please take that printed samples are for reference only. Pad printing sample has been made with two cycles.



Converting



Slitting



Perforated



Packaging



Rolls



Spools



Shipping boxes



Labels



Scored cut



Mated



Custom manufactured straps



Complete product assembly



Sealed bag



Blister



Folding boxes



Bundling



Bulk




Customised packaging




2 layers laminate

BASIC PRODUCT CONSTRUCTION





BASIC PRODUCT CONSTRUCTION



5 layers laminate

BASIC PRODUCT CONSTRUCTION

