

## PRODUCT DATA

**EMI.2800**

### POLYFOAM SEALANT TAPE

**DESCRIPTION:** EMI.2800 is a pressure sensitive foam sealing tape with a highly aggressive synthetic rubber adhesive coated one side. Cross- linked polyethylene foam provides superior strength and durability. Combines good initial tack with high shear and peel strength. Good conformance to textured and rough surfaces. Closed cell. Available in black and white.

**APPLICATION IDEAS:** Suitable for use on polyethylene, polypropylene and other difficult to bond surfaces. Bonds well to low surface energy surfaces.

### TECHNICAL DATA

FOAM THICKNESS	1/32" – 1/4"
TACK @ 72 Deg. F	80 + oz./in
ADHESION	
Peel	100 + oz./in-width
Shear	1000 + hours / 1000 g
TEMPERATURE RESISTANCE	to 165 Deg. F
RELEASE LINER	60 lb. Moisture Stable

### TEST METHODS:

All test procedures used are in accordance with ASTM and PSTC methods.



### ***Technical Information***

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Engineered Materials believes are reliable, but the accuracy or completeness of such information is not guaranteed.

### ***Product Use***

Many factors beyond Engineered Materials control and uniquely within user's knowledge and control can affect the use and performance of an Engineered Materials product in an application. Given the variety of factors that can affect the use and performance of an Engineered Materials product, user is solely responsible for evaluating the product and determining whether it is fit for a particular purpose and suitable for user's method of application.

### ***Limited Remedy***

Engineered Materials warrants for 12 months from the date of shipment that the product Engineered Materials produced, will be free of defects in material and manufacture. Engineered Materials MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover damage resulting from the use or inability to use Engineered Materials product due to misuse, workmanship in application, or application or storage not in accordance with Engineered Materials recommended procedures. If the Engineered Materials product is proved to be defective within the warranty period stated above, THE EXCLUSIVE REMEDY, AT Engineered Materials OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE product. Engineered Materials shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.