QS. FORM 25 July 30, 2009 Page 1 of 1



Velcro USA Inc.

# **Technical Data Sheet**

## HI-AIR® Brand Fastener Hook

## **Material Description**

Name:	Hook 66-0399 Nylon [Nomex FR yarns]	
Material:		
Color:	Natural #017	

#### **Dimensional Specifications**

Width:	+/- 1/16 inch [+/-1.6 mm]	
Weight <sup>2</sup> :	6.6 gram per one inch yard (min. avg.) $[284.2 \text{ g/m}^2]$	
Thickness:	0.050 inches (minimum) [1.27 mm]	
Roll Length:	<100 yards (-0, +12 inches) [91.4 +0.3m]	
	= />100 yards (-0, +1% of target value) [91.4m +1% target]	

Contact your Customer Relations Specialist for more available colors and widths.

## **Performance Specifications**

Testing	Minimum	Test Method
Closure Peel Strength <sup>3</sup>	0.50 PIW [0.876 N/cm]	40011
Closure Shear Strength <sup>3</sup>	10.0 Lbs. <sup>4</sup> [1.81 N]	40012
Flammability Testing	Max. Burn Length Avg. 8.0"	FAR 25.853, 12 sec.
	Max Flame Time Avg. 15 sec	
	Max Drip Time Avg. 5 sec.	

Tested with: Loop 003

<sup>2</sup> Reference Internal Specification Only. (Actual weight varies per width)

- <sup>3</sup> After Mil-Spec Laundering per AATCC 61
- <sup>4</sup> Reference 1 x 2 inch test area (other Shear results vary per tape width)

#### **Requirements**

Velcro® brand Hook 66-0399; meets the requirements of Mil-Spec A-A-55126 rev. B

Rev. Date: 04-29-2010

406 Brown Ave • Manchester, New Hampshire 03103 Telephone: (603) 669-4880 • Fax: (603) 669-3086